



Aiface Orcus

| | |
|--------------------------------|--|
| Display | 2.4"@ TFT Color LCD Screen (320*240) |
| Camera | WDR Binocular Camera @ 1MP |
| Operation System | Linux |
| Hardware | CPU: Dual Core@1GHz RAM: 512MB; ROM: 8GB |
| Multiple Authentication method | Fingerprint / Face / Card / Password |
| Fingerprint Template Capacity | 3,000 |
| Face Template Capacity | 1,500 |
| Card Capacity | 3,000 |
| User Capacity | 3,000 |
| Transaction Capacity | 1,50,000 |
| Biometric Authentication Speed | Fingerprint: <0.5 sec; Facial Authentication: <0.35 sec |
| Facial Authentication Distance | 30cm to 200cm |
| False Acceptance Rate (FAR) % | Visible Light Facial Authentication : FAR ≤ 0.01% Fingerprint : FAR ≤ 0.0001% |
| False Rejection Rate (FRR) % | Visible Light Facial Authentication : FRR ≤ 0.02% Fingerprint : FRR ≤ 0.01% |

| | |
|--------------------------|---|
| Available RFID Module | Proximity Card@125 kHz (Standard) Mifare Card@13.56 MHz (Optional) |
| Communication | TCP/IP, Wi-Fi, USB |
| Access Control Interface | Electro Magnetic Lock/ Electric Lock, Door Sensor, Exit Button |
| Power Supply | DC 12V 1.5A |
| Operating Temperature | -5°C to 45°C |
| Operating Humidity | 20% to 80% RH (Non-condensing) |
| Dimensions | 205.20 mm*74.19 mm*33.30 mm (L*W*H) |
| Supported Software | eTimetracklite Software, eBioServer |

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.