

HC-IPC-T4214A-0360-LED



Product Features

- ≥ Day/night functionality
- ≥ Max. resolution: 2560 x1440
- ≥ ICR auto switch, true day / night,
- ≥ 30m IR night view distance
- ≥ Built-in mic
- ≥ 3D DNR, Digital WDR, HLC, BLC, Defog
- ≥ PoE Power Supply (optional)
- ≥ Support mobile surveillance by smart phones with iOS and Android OS
- ≥ IP67 Ingress Protection



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/2.7" CMOS
Effective Pixels	2560 x1440
Electronic Shutter Speed	Auto/Manual, 1/6~1/10,000 s
Min.Illumination	Colour: 0.012 Lux (F1.6, AGC ON) 0 Lux with IR
Iris Type	Fixed Iris

LENS

Lens	2.8mm @F1.85, horizontal field of view:107°/ 3.6mm @F1.6, horizontal field of view:93.7°/ 6mm@F1.85,horizontal field of view:56° (optional)*
Lens Mount	M12
IR Distance	30m
Wide Dynamic Range	Digital WDR
Digital NR	2D/3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~75°; Rotation: 0°~360°

IMAGE

Video Compression	H.265, H.264, MJPEG
H.265 Compression Standard	Main Profile @Level4.1 High Tier
Resolution	4MP (2560 x1440), 3MP (2304 x 1296), 1080P (1920x1080),720P (1280x720), D1, CIF, 480x240
Main Stream	4MP(1~20fps)/3MP(1~30fps)/1080P(1~30fps)
Bit Rate Type	VBR/CBR
Image Settings	Saturation, Brightness, Chroma, Contrast Wide Dynamics, Sharpen, NR, etc. adjustable through Client Software or Web browser



FUNCTIONS

Remote Monitoring
Online Connection

Web Browsing, CMS Remote Control
Support Simultaneous monitoring for upto 4users
Support Multi-Stream Real Time Transmission

Audio
Network Protocol

Built-in Mic
UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS,
SMTP, FTP, 802.1x, UPnP, HTTP,HTTPs,QoSStorage

Smart Alarm
PoE

Motion detection
Optional

INTERFACE

Network

1RJ45 10/100 Base-TX Ethernet

ELECTRICAL

Power Supply
Power Consumption

DC 12V (PoE optional)
< 5W

ENVIRONMENTAL

Operating Conditions
Ingress Protection

-20°C ~ 55°C (-4°F~131°F) Humidity
IP67



An ISO 9001:2008 Certified Company