

HD-NVR-4104T



Product Features

- 4 CH Support 6MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion
- Playback : 4 / 8 CH simultaneously playback
- Search: time slice, time, event (manual, Sensor, Motion), tag search
- Express and flexible backup via USB, network and so on Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, and CMS supported
- Remote control via IE or CMS : Preview, Playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log review and device status review
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR Code Scanning by Mobile Phone and PAD
- Powerful Smart Phone&Pad Surveillance with iOS and Android OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

Compression	H.265 Standard
Main Processing Chip	Hi3536D
OS	Embedded Linux

VIDEO

Incoming Bandwidth	40 Mbps
Outcoming Bandwidth	40 Mbps
Video Compression	Smart H.265, H.265, H.264
Input Resolution	6MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P real time
Network Access	4 CH IPC Input
Output	HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768

AUDIO

Input	4 CH IPC Audio Input
Local Output	No (HDMI supports the audio output)
Compression	G.711(U/A)

RECORD

Resolution	6MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P
Frame Rate	30fps/25fps(NTSC/PAL)
Bit Rate	32Kbps~6Mbps
Image Quality	5 Level

PLAYBACK

Simultaneous Playback	Max 4 CH
-----------------------	----------

NETWORK

Interface	RJ45 10/100Mbps × 1
Network Protocol	IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF

STORAGE

HDD	SATA×1
Max Capacity for 1 single HDD	8T



An ISO 9001:2008 Certified Company

BACKUP

USB Backup Yes

INTERFACE

USB USB 2.0 ×2

ELECTRICAL

Power Supply DC 12V
Consumption ≤ 5W (without HDD)

ENVIRONMENTAL

Working Environment -10 ~ 50 °C, 10% ~ 90% humidity
Dimension(mm) 255 × 222 × 42 (W × D × H)
Case Mini 1U



An ISO 9001:2008 Certified Company