

# PT-HTD110E-IP

## 2 MP IR Bullet Camera



### Key Features

- 2 MP high performance CMOS
- 1920 × 1080 resolution
- 3.6 mm fixed lens
- Up to 20 m IR distance
- OSD menu, DNR, DWDR
- Analog HD output
- IP66
- Up the coax (PRAMA)

## Specifications

<i>Camera</i>	
Image Sensor	2 MP CMOS image sensor
Signal System	PAL/NTSC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Resolution	1920 (H) × 1080 (V)
Min. illumination	0.02 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens	3.6 mm fixed lens
Horizontal Field of View	103° (2.8 mm), 82.2° (3.6 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Synchronization	Internal synchronization
WDR (Wide Dynamic Range)	DWDR
<i>Menu</i>	
Image Mode	STD/HIGH-SAT
AGC	Support
Day/Night Mode	Smart/color/BW(Black and White)
Backlight Compensation	Support
DWDR	Support
Language	English
Functions	Brightness, Sharpness, DNR, Mirror
<i>Interface</i>	
Video Output	1 HD analog output
<i>General</i>	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity 90% or less (non-condensation)
Power Supply	12 VDC±15%
Power Consumption	Max. 4 W
Ingress Protection	IP66
Material	Plastic
IR Range	Up to 20 m

\*Specifications are subject to change without prior notice. \*Product picture may differ from the actual.

## Available Model

PT-HTD110E-IP