

Smart 4G 3MP Dome Camera



FEATURES

- 3 MP Resolution
- 4G with SD Card support
- Two way audio communication
- Built-in high sensitivity mic and speaker
- Intelligent human detection algorithm for effective alarms
- Area movement detection with real-time push information
- Mobile app and PC client software for remote monitoring



4G



SD
Card



Human
Detection



2 Way
Audio Comm



Voice
Prompt

Technical Specifications

| | |
|----------------------|--|
| Product code | T18021 |
| Image Sensor | 1/2.7" CMOS Sensor |
| Resolution | 2304x1296 |
| S/N Ratio | > 39.1 dB |
| Minimum Illumination | Color: 0.001 Lux, BW: 0 Lux |
| Lens | 3.6mm M12 Mount |
| LED | 2 Infrared Array |
| Infrared IR distance | >20 Meters |
| Image settings | Standard, Bright and Gorgeous (adjust the settings through TRUECLOUD APP) |
| OSD | Date, Time & Title |
| White Balance | Auto |
| Day & Night | Auto / Color / B & W |
| 3D-DNR | Auto |
| Mirror/Flip | On / Off |
| Video Streaming | H.264 / H.264+ / H265 / H.265+ 2048 x 1536 @ 15 fps H.264 / H.264+ / H265 / H.265+ 640 x 480 @ 15 fps |
| Features | Motion detection, alarm information push, mobile phone, client remote monitoring |
| Audio Streaming | AAC/G711A |
| Audio IN | Built in mic |

| | |
|--------------------------------|--|
| Audio Out | Built in Speaker |
| Button | Reset |
| TF /SD card | 128GB max |
| Protocol | N1 |
| Connectors | RJ 45 / Power input |
| Connection mode | 4G/ Network cable |
| Light Mode | Blink means confiture mode, On means connection mode |
| Thunder Prevention | Standard IEC61000-4-5 |
| Power Input | 12V/2A DC |
| Thunder Prevention | Standard IEC61000-4-5 |
| Power Consumption | ≤5.6W |
| Operation Temperature/Humidity | -10°C ~ +50°C / 30% to 80% RH |
| Storage Temperature/Humidity | -20°C ~ +60°C / 20% to 90% RH |
| Dimension | (H)100*(W)117*(D)117 |
| Housing Type | Plastic Housing |
| Weight Net | 0.298KG |
| Weight Gross | 0.320KG |